

Technical Data Sheet

EXTASE clear

Order no.:	277 373	
Product designation:	Safety Spectacle EXTASE clear	
Applied standard:	DIN EN 166 (DIN = German Institute for Standardization)	
Utilization:	<p>The safety spectacle is ideal for factory visitors, assembly workers and laboratory workers. It can be carried in connection with half masks or filtering half masks.</p> <p>The scope of protection is determined by the product information, technical standards and valid application rules.</p>	
Description:	The safety spectacle encloses the eye range.	
Materials:	Frame Nose pad upholstery Temple upholstery Mounting screw Lens	Polycarbonate Polyvinyl chloride Thermoplastic rubber Metal Polycarbonate
Colour of frame:	silver-grey / green	
Lens thickness:	1,3 mm – 2,3 mm	
Lenses colour:	clear	
Weight:	approx. 33 gram	
Marking:	Trade mark of manufacturer (LOGO) Product designation Applied standard CE-Identification Optical class Operating range Protection level of the eyeglass filters Abbreviation for mechanical firmness	
Marking explanation:	1 Optical class (particularly high requirement of the visual efficiency) 2-1.2 Protection level of the eyeglass filters (ultraviolet protection filter) FT Mechanical firmness – Impact with low energy at extreme temperatures (-5°C to 55°C)	
Properties:	Anti-Scratch Anti-Fog 100,00% UV-Protection	
Handling:	Take the Safety spectacles from the packing directly before use. Use the Safety spectacles in accordance with the information brochure.	
Storage conditions:	Ambient temperature. Protect against cold, heat and humidity. Consider conditions noted on the information brochure.	
Warning reference:	Please consider the information brochure!	
User references:	EKASTU Safety GmbH guarantees the indicated achievement according to class and type. It is to be noted that the laboratory test values can considerably deviate from those which are reached in practice. This can lead to longer or shorter preservation time. The user must read and understand all functional information. In addition, the knowledge of all relevant application rules absolutely necessary (in particular the application rules according to BGR 192 (use of ocular protection and facial protection)).	