

## Technical Data Sheet

**C 607/Silicone/TR**

<b>Order no.:</b>	466 616	
<b>Product designation:</b>	Full Face Mask C 607/Silicone/TR (Class 2)	
<b>Applied standard:</b>	DIN EN 136 (DIN = German Institute for Standardization)	
<b>Utilization:</b>	<p>In connection with respiratory filter (standard thread DIN EN 148-1) as filtering device, in connection with powered filtering device as filtering device, in connection with compressed air line device as breathing apparatus and in connection with unassisted fresh air hose breathing device as breathing apparatus.</p> <p>The scope of protection is determined by the product information, technical standards and valid application rules.</p>	
<b>Description:</b>	Faceblank enclose the entire face.	
<b>Materials:</b>	<ul style="list-style-type: none"> <li>Faceblank</li> <li>Fastener for head harness</li> <li>Head harness</li> <li>Carrying strap</li> <li>Inner mask</li> <li>Check valve</li> <li>Disk-Frame</li> <li>Lens</li> <li>Inhalation- and Exhalation valve</li> <li>Exhalation valve clip</li> <li>Exhalation valve cap</li> <li>Connector</li> <li>Connector-Clip</li> <li>Speech diaphragm</li> </ul>	<ul style="list-style-type: none"> <li>Silicone</li> <li>Fiber glass reinforced plastic / Metal</li> <li>EPDM (Ethylene-Propylene-Diene-Mixture)</li> <li>Polyvinyl chloride</li> <li>EPDM (Ethylene-Propylene-Diene-Mixture)</li> <li>Rubber</li> <li>Polyphenylene oxide</li> <li>Laminated safety glass (triplex)</li> <li>Rubber</li> <li>Metal</li> <li>Polyethylene</li> <li>Fiberglass reinforced plastic</li> <li>Metal</li> <li>Metal</li> </ul>
<b>Weight:</b>	approx. 580 g	
<b>Inhalation resistance:</b>	<p>at 30 l/min, constant flow max. 0.5 mbar (EN 136)</p> <p>at 95 l/min, constant flow max. 1.5 mbar (EN 136)</p> <p>at 160 l/min, constant flow max. 2.5 mbar (EN 136)</p>	
<b>Exhalation resistance:</b>	at 160 l/min, constant flow max. 3.0 mbar (EN 136)	
<b>Marking:</b>	<p>Trade mark of manufacturer (LOGO)</p> <p>Product designation</p> <p>Applied standard</p> <p>Manufacture year and -month</p> <p>CE-Identification</p> <p>Notified body</p> <p>Type identifying marking</p>	
<b>Handling:</b>	<p>Take the Full face mask from the Packing and/or Storage container directly before use.</p> <p>Use the Full face mask in accordance with the information brochure.</p>	
<b>Storage conditions:</b>	<p>Ambient temperature. Protect against cold, heat and humidity.</p> <p>Consider conditions noted on the packaging.</p>	
<b>Warning reference:</b>	Please consider the information brochure!	
<b>User references:</b>	<p>EKASTU Safety GmbH guarantees the indicated achievement according to class and type.</p> <p>It is to be noted that the laboratory test values can considerably deviate from those, which are reached in practice. The user must read and understand all functional information. Use the Respiratory protective devices with this information brochure, the relevant valid statutory regulations and the safety requirements of the profession associations, particularly the regulations for use in accordance with DGUV Rule 112-190 resp. DIN EN 529 'Respiratory protective devices – recommendation for selection, use, care and maintenance – guidelines'.</p>	

TD 466616 English 05-07.17