EKASTU | Safety WIR PRODUZIEREN SICHERHEIT!

Technical Data SheetCompressed Air Tube for
Respiratory Protective Devices 5m

144 805	
Compressed air tube for respiratory protective devices 5m	
DIN EN 14953 and DIN EN 14954 (DIN = German Institute for Standardization)	
Use as compressed air tube for respiratory protective devices in connection with Compressed air line unit AIRLINE FC 1002, Compressed air line unit AIRLINE AP 2002 and Shotblasting Protective Helmet P4/C4. The scope of protection is determines by the product information, technical standards and valid application rules.	
The compressed air tube for respiratory protective device leads the required breathable air from extraction point to the respiratory protective device. The hose lining is made from materials free from any dangerous products for inhaled air.	
Compressed air tube Hose sleeves Safety male coupling nipple Safety female coupling	Ethylene-Propylene-Diene-Mixture (EPDM) (reinforced by synthetic fibres) Steel Chromium-plated Steel Chromium-plated Steel
approx. 1400 g	
max. 10 bar	
-30°C to +120°C	
Trade mark of manufacturer (LOGO) Product designation Applied standard Manufacture year and -month	
Take the compressed air tube for respiratory protective devices from the storage case directly before use. Use the compressed air tube for respiratory protective devices in accordance with the information brochure.	
Ambient temperature. Protect against cold, heat and humidity.	
Please consider the information brochure!	
EKASTU Safety GmbH guarantees the indicated achievement according to class and type. It is to be noted that the laboratory test values can considerably deviate from those, which are reached in practice. The user must read and understand all functional information. Use the Respiratory protective devices with this information brochure, the relevant valid statutory regulations and the safety requirements of the profession associations, particularly the regulations for use in accordance with DGUV Rule 112-190 resp. DIN EN 529 'Respiratory protective devices – recommendation for selection, use, care and maintenance – guidelines'.	
	Compressed air tube for respiratory pro- DIN EN 14953 and DIN EN 14954 (DIR Use as compressed air tube for respirator and Shotblasting Protective Helmet P44 The scope of protection is determines valid application rules. The compressed air tube for respirator air from extraction point to the respirator approx. 1400 g max. 10 bar -30°C to +120°C Trade mark of manufacturer (LOGO) Product designation Applied standard Manufacture year and -month Take the compressed air tube for resp directly before use. Use the compresses accordance with the information broch Ambient temperature. Protect against of Please consider the information broch EKASTU Safety GmbH guarantees the type. It is to be noted that the laborator which are reached in practice. The use information. Use the Respiratory prote relevant valid statutory regulations and associations, particularly the regulatior resp. DIN EN 529 'Respiratory protection associations, particularly the regulation