

## Technical Data Sheet

## Fresh Air Hose L5/5m long, ANT

<b>Order no.:</b>	155 605														
<b>Product designation:</b>	Fresh air hose L5/5m long, ANT														
<b>Applied standard:</b>	DIN EN 138 (DIN = German Institute for Standardization)														
<b>Utilization:</b>	Use as fresh air hose in connection with Unassisted fresh air hose breathing apparatus 6500 and Fresh air hose breathing apparatus 6501. The scope of protection is determined by the product information, technical standards and valid application rules.														
<b>Description:</b>	The fresh air hose made from soft plastic with integrated spiral made of especially robust plastic and copper wire inside (Patent Pending) for grounding feasibility. The fresh air hose leads the required breathable air from an area beyond the contaminated surrounding atmosphere to the facepiece of fresh air hose breathing apparatus.														
<b>Materials:</b>	<table><tr><td>Spiral coiled tube</td><td>Soft plastic</td></tr><tr><td>Hose sleeves</td><td>Steel</td></tr><tr><td>MS-Coupling</td><td>Brass</td></tr><tr><td>Wire</td><td>Copper</td></tr><tr><td>Steel cable</td><td>Steel with PVC sheathing</td></tr><tr><td>Ferrules</td><td>Copper</td></tr><tr><td>Plug-in iron piece</td><td>Galvanized sheet steel</td></tr></table>	Spiral coiled tube	Soft plastic	Hose sleeves	Steel	MS-Coupling	Brass	Wire	Copper	Steel cable	Steel with PVC sheathing	Ferrules	Copper	Plug-in iron piece	Galvanized sheet steel
Spiral coiled tube	Soft plastic														
Hose sleeves	Steel														
MS-Coupling	Brass														
Wire	Copper														
Steel cable	Steel with PVC sheathing														
Ferrules	Copper														
Plug-in iron piece	Galvanized sheet steel														
<b>Weight:</b>	approx. 2000 g														
<b>Operating pressure:</b>	max. 7 bar														
<b>Resistance to temperature:</b>	-5°C to +65°C														
<b>Marking:</b>	Manufacturer Product designation Manufacture year and -month														
<b>Handling:</b>	Take the fresh air hose from the storage case directly before use. Use the fresh air hose in accordance with the information brochure.														
<b>Storage conditions:</b>	Ambient temperature. Protect against cold, heat and humidity.														
<b>Warning reference:</b>	Please consider the information brochure! Proper grounding has to be guaranteed by the user.														
<b>User references:</b>	EKASTU Safety GmbH guarantees the indicated achievement according to class and type. It is to be noted that the laboratory test values can considerably deviate from those, which are reached in practice. The user must read and understand all functional information. Use the Respiratory protective devices with this information brochure, the relevant valid statutory regulations and the safety requirements of the profession associations, particularly the regulations for use in accordance with DGUV Rule 112-190 resp. DIN EN 529 'Respiratory protective devices – recommendation for selection, use, care and maintenance – guidelines'.														