EKASTU | Safety WIR PRODUZIEREN SICHERHEIT!

Technical Data Sheet		Fresh Air Hose L20/20m
Order no.:	155 812	
Product designation:	Fresh air hose L20/20m	
Applied standard:	DIN EN 138 (DIN = German Institute for Standardization)	
Utilization:	Use as fresh air hose in connection with Fresh air hose breathing apparatus 6501. The scope of protection is determines by the product information, technical standards and valid application rules.	
Description:	The fresh air hose made from soft plastic with integrated spiral made of especially robust plastic. The fresh air hose leads the required breathable air from an area beyond the contaminated surrounding atmosphere to the facepiece of fresh air hose breathing apparatus.	
Materials:	Spiral coiled tube Hose sleeves MS-Coupling	Soft plastic Steel Brass
Weight:	approx. 6100 g	
Operating pressure:	max. 7 bar	
Resistance to temperature:	-5°C to +60°C	
Marking:	Manufacturer Product designation Manufacture year and -month	
Handling:	Take the fresh air hose from the storage case directly before use. Use the fresh air hose in accordance with the information brochure.	
Storage conditions:	Ambient temperature. Protect against cold, heat and humidity.	
Warning reference:	Please consider the information brochure!	
User references:	EKASTU Safety GmbH guarantees the indicated achievement according to class and type. It is to be noted that the laboratory test values can considerably deviate from those, which are reached in practice. The user must read and understand all functional information. Use the Respiratory protective devices with this information brochure, the relevant valid statutory regulations and the safety requirements of the profession associations, particularly the regulations for use in accordance with DGUV Rule 112-190 resp. DIN EN 529 'Respiratory protective devices – recommendation for selection, use, care and maintenance – guidelines'.	