

Technical Data Sheet

Polimask GAMMA/Silicone

Order no.:	433 227												
Product designation:	Half Mask Polimask GAMMA/Silicone												
Applied standard:	DIN EN 140 (DIN = German Institute for Standardization)												
Utilization:	In connection with respiratory filter of the series 230 (special thread 95mm) as filtering device. The scope of protection is determined by the product information, technical standards and valid application rules.												
Description:	Faceblank enclose the nose, mouth and chin.												
Materials:	<table><tr><td>Faceblank</td><td>Silicone</td></tr><tr><td>Fastener for head harness</td><td>Plastic (ABS)</td></tr><tr><td>Head harness</td><td>Textile elastic band / Polypropylene</td></tr><tr><td>Inhalation- and Exhalation valve</td><td>Rubber</td></tr><tr><td>Exhalation valve fit</td><td>Plastic (ABS)</td></tr><tr><td>Filter connector</td><td>Polypropylene</td></tr></table>	Faceblank	Silicone	Fastener for head harness	Plastic (ABS)	Head harness	Textile elastic band / Polypropylene	Inhalation- and Exhalation valve	Rubber	Exhalation valve fit	Plastic (ABS)	Filter connector	Polypropylene
Faceblank	Silicone												
Fastener for head harness	Plastic (ABS)												
Head harness	Textile elastic band / Polypropylene												
Inhalation- and Exhalation valve	Rubber												
Exhalation valve fit	Plastic (ABS)												
Filter connector	Polypropylene												
Weight:	approx. 165 g												
Inhalation resistance:	at 30 l/min, constant flow max. 0.5 mbar (EN 140) at 95 l/min, constant flow max. 1.3 mbar (EN 140) at 160 l/min, constant flow max. 2.0 mbar (EN 140)												
Exhalation resistance:	at 160 l/min, constant flow max. 3.0 mbar (EN 140)												
Marking:	Trade mark of manufacturer (LOGO) Product designation Applied standard Manufacture year and -month CE-Identification Notified body Type identifying marking												
Handling:	Take the Half mask from the Packing and/or Storage container directly before use. Use the Half mask in accordance with the information brochure.												
Storage conditions:	Ambient temperature. Protect against cold, heat and humidity. Consider conditions noted on the packaging.												
Warning reference:	Please consider the information brochure!												
User references:	EKASTU Safety GmbH guarantees the indicated achievement according to class and type. It is to be noted that the laboratory test values can considerably deviate from those, which are reached in practice. The user must read and understand all functional information. Use the Respiratory protective devices with this information brochure, the relevant valid statutory regulations and the safety requirements of the profession associations, particularly the regulations for use in accordance with DGUV Rule 112-190 resp. DIN EN 529 'Respiratory protective devices – recommendation for selection, use, care and maintenance – guidelines'.												