



Order no.: 466 607

**Product designation:**

Full Face Mask C 607/F (Class 3)

In connection with respiratory filter (standard thread DIN EN 148-1) as filtering device, in connection with powered filtering device as filtering device, in connection with compressed air line device as breathing apparatus and in connection with unassisted fresh air hose breathing device as breathing apparatus.

The scope of protection is determined by the product information, technical standards and valid application rules.



## DESCRIPTION

- **Compact full face mask**, fitting any face conformations.
- Polycarbonate visor with high impact resistance to acids, even at high concentrations.
- Excellent voice transmission thanks to the frontal position of the speech diaphragm.

## MAIN FEATURES



Five straps elastic harness made of rubber, with quick release buckles.

Synthetic rubber face piece with wide internal seal for a tight fit and adjustable fasteners for the attachment of the harness (patented).

Inner mask with non return valves.

Two exhalation valves with compensating prechambers.

Wide field of vision and distortion free visor made of polycarbonate, with fiberglass reinforced synthetic resin frame, easily replaceable.

Threaded connector conforming with European EN 148/1 standard, with speech diaphragm.

## PERFORMANCES



Sturdiness



Comfort



Panoramic view



Ergonomics



Easy maintenance

## APPLICATION FIELDS



Marine



Industry



Hospital



Chemical Pharmaceutical Industry



Agriculture

## MATERIALS

- Face seal: Ethylene-Propylene-Diene-Mixture (EPDM)
- Inner half mask: Ethylene-Propylene-Diene-Mixture (EPDM)
- Disk-Frame: Polyphenylene oxide (PPO)
- Visor: Polycarbonate (PC)
- Inhalation valve: Silicone
- Connector: Polyamide (PA)
- Connector-Clip: Metal
- Harness: Ethylene-Propylene-Diene-Mixture (EPDM)

## WEIGHT

- approx. 520 g

## MARKING

- Trade mark of manufacturer (LOGO)
- Product designation
- Applied standard
- Manufacture year and -month
- CE-Identification
- Notified body
- Type identifying marking

## DONNING AND USING

- Take the Full face mask from the Packing and/or Storage container directly before use.
- Use the Full face mask in accordance with the information brochure.

## STORAGE

- Ambient temperature. Protect against cold, heat and humidity.
- Consider conditions noted on the packaging.

## CERTIFICATIONS

The mask is certified as class 2 according to EN 136 (maximum mechanical, heat and flame resistance).  
For use with particle, gas and combined filters equipped with EN 148/1 threaded connection.  
Certified according to European Regulation (EU) 2016/425.

## USER REFERENCES

EKASTU Safety GmbH guarantees the indicated achievement according to class and type. It is to be noted that the laboratory test values can considerably deviate from those, which are reached in practice. The user must read and understand all functional information. Use the Respiratory protective devices with this information brochure, the relevant valid statutory regulations and the safety requirements of the profession associations, particularly the regulations for use in accordance with DGUV Rule 112-190 resp. DIN EN 529 „Respiratory protective devices – recommendation for selection, use, care and maintenance – guidelines“.

TD 466607 English\_06-01.24