




Order no.: 466 608

Product designation:

Full Face Mask SFERA (Class 3)

In connection with respiratory filter (standard thread DIN EN 148-1) as filtering device, in connection with powered filtering device as filtering device, in connection with compressed air line device as breathing apparatus and in connection with unassisted fresh air hose breathing device as breathing apparatus.

The scope of protection is determined by the product information, technical standards and valid application rules.



DESCRIPTION

- Extra wide view full face mask.
- Multipurpose connector and accurate distribution of weights.
- Wide field of vision: over 85% of the natural field.
- Full face polycarbonate visor with a high impact resistance, completely free from distortions.
- Resistance to flame and radiant heat: the mask is self-extinguishing and retains its protective capacity even after such severe tests.
- Quick donning and doffing; the shoulder strap allows to keep the mask ready for immediate use.
- Long shelf life: high ozone resistance of the rubber compounds used.
- Easy maintenance, washing and disinfection: all components can be disassembled with simple tools.
- Neck strap for suspending the mask when not being used.
- Comfortable harness fixed on 5 points made of EPDM

MAIN FEATURES



PERFORMANCES



Sturdiness



Comfort



Panoramic view



Ergonomics



Easy maintenance

APPLICATION FIELDS



Marine



Industry



Hospital



Chemical Pharmaceutical Industry



Agriculture

MATERIALS

- Face seal: Ethylene-Propylene-Diene-Mixture (EPDM)
- Inner half mask: Ethylene-Propylene-Diene-Mixture (EPDM)
- Disk-Frame: Polyphenylene oxide (PPO)
- Heat conduction plate: Metal
- Visor: Polycarbonate (PC)
- Check valve: Rubber
- Inhalation valve: Rubber
- Exhalation valve: Rubber
- Connector: Polyamide (PA)
- Harness: Ethylene-Propylene-Diene-Mixture (EPDM)

WEIGHT

- approx. 650 g

MARKING

- Trade mark of manufacturer (LOGO)
- Product designation
- Applied standard
- Manufacture year and -month
- CE-Identification
- Notified body
- Type identifying marking

DONNING AND USING

- Take the Full face mask from the Packing and/or Storage container directly before use.
- Use the Full face mask in accordance with the information brochure.

STORAGE

- Ambient temperature. Protect against cold, heat and humidity.
- Consider conditions noted on the packaging.
- Not higher than 50°C

CERTIFICATIONS

The mask is certified as class 3 according to EN 136 (maximum mechanical, heat and flame resistance).
For use with particle, gas and combined filters equipped with EN 148/1 threaded connection.
Certified according to European Regulation (EU) 2016/425.

USER REFERENCES

EKASTU Safety GmbH guarantees the indicated achievement according to class and type. It is to be noted that the laboratory test values can considerably deviate from those, which are reached in practice. The user must read and understand all functional information. Use the Respiratory protective devices with this information brochure, the relevant valid statutory regulations and the safety requirements of the profession associations, particularly the regulations for use in accordance with DGUV Rule 112-190 resp. DIN EN 529 „Respiratory protective devices – recommendation for selection, use, care and maintenance – guidelines“.

TD 466608 English_06-01.24